

## Mains Fed Water Cooler

Water Cooler designed and built to provide infection prevention and water safety with healthcare facilities in mind. Built with anti-bacterial stainless-steel body, providing water at between 8-10 degrees at 35 - 40 litres per hour.

### Key Features:

- Main fed water cooler with inline 10-micron filter that can be change based on individual requirements.
- All components help to prevent growing of water micro-organisms and all components WRAS approved.
- Internal copper pipework throughout.
- Anti-bacterial dispense button located at the top of unit at an accessible height, to enable easy access for all users including those in wheelchairs or with restricted mobility. A foot operated unit is also available upon request.
- Replaceable anti-bacterial dispense button
- All drips from the nozzle are channelled directly into the waste outlet to prevent water standing in a drip tray.

### Specification:

#### External Fabric

- 316 Stainless Steel Body with sloping top
- Inline 10-micron filter can be installed onto mains pipework going into water dispenser.

#### Internal Fabric

- Internal funnel and drip outlet cover, ½" bulkhead copper feed to 8mm internal copper pipework throughout
- No plastic pipework
- Local isolation valve
- Internal double check valve
- Outlet can only accommodate 7 oz cup preventing water bottles from being used to stop cross contamination.
- Easy to maintain and service with service contracts available upon request.

#### Dimensions

- Floor standing unit is 1200mm h x 340mm w x 380mm d, however worktop mounted cooler or bespoke sizing available upon request.

#### Electrical requirements

- 230V supply with kettle lead fitting.
- Heat resistant plastic around electrical circuit areas.

### Dispensing button

- Anti-bacterial nozzle that can be replaced every month.
- Foot pedal option also available.

### Water Temperature

- Mains fed water consistently providing between 8-10 degrees dispensing water at 35-40 litres per hour.

### Waste Outlet

- 1 ¼" plastic waste trap with P trap

### Cup holder

- 7 oz stainless steel cupholder can be provided on the side of unit upon request for additional cost.

